

Application No.: 10/719,371

2 Docket No.: 28212/1200285-US1/NC34963US

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A system for configuring differentiated services (Diffserv) over multi-protocol label switching (MPLS) in a network that includes MPLS tunnels, comprising:

a policy server that is arranged to configure a customer policy and a mapping policy that maps between an experimental (EXP) field and a unique per-hop-behavior (PHB), and to deploy the mapping policy and the customer policy to interfaces of devices of the network that correspond to the tunnels, wherein the interfaces and the customer policy are associated with a same role name.

2. (Original) The system of claim 1, wherein

the customer policy comprises a tunnel group identifier and tunneling mode.

3. (Original) The system of claim 1, wherein

the policy server translates the mapping policy into device specific commands, and

deployment is performed by deploying commands to specific devices.

4. (Original) The system of claim 1, wherein

deployment is such that the interfaces associate with at least one of input roles, output roles and MPLS gateways of customer source and destination host groups.

5. (Currently amended) An apparatus for configuring Diffserv over MPLS in a network, comprising:

a memory;

a service application residing on the memory,

{S:\28212\1200285-us1\80037719.DOC (XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX) }

Application No.: 10/719,371

3 Docket No.: 28212/1200285-US1/NC34963US

wherein the service application is arranged to configure a customer policy that comprises a tunnel group and tunneling mode, the customer policy being arranged to have customer traffic mapped into MPLS tunnels, and

wherein the service application is arranged to configure an EXP-to-PHB mapping policy that is arranged to map EXP fields to PHB;

a central processing facility that is arranged to translate the customer policy and mapping policy into device-neutral policy parameters; and

a policy consumer that is arranged to translate the device-neutral policy parameters into device-specific commands, and that is further arranged to deploy the device-specific commands to policy targets, such that the customer policy and mapping policy are implemented across at least a portion of the network, and wherein the policy targets each include an interface associated with a role name that is also associated with the customer policy.

6. (Original) The apparatus of claim 5, further comprising:

a user interface that is arranged to receive the customer policy and the mapping policy.

7. (Original) The apparatus of claim 5, wherein

deployment is such that the interfaces associate with at least one of input roles, output roles and MPLS gateways of customer source and destination host groups.

8. (Original) The apparatus of claim 5, wherein

the policy consumer is further arranged to attach the customer policy to the corresponding MPLS tunnels and deploy the customer policy to interfaces of the attached MPLS tunnels.

{S:\28212\1200285-us1\80037719.DOC (10/30/2005 15:30 FAX 2062628901)}

Application No.: 10/719,371

5 Docket No.: 28212/1200285-US1/NC34963US

defining a mapping policy configured to map between an EXP field and a unique PHB;

defining a customer policy that is configured to govern the treatment of individual customer traffic;

defining a network policy that is configured to define the Diffserv treatment of aggregated traffic;

translating the mapping policy, the network policy and the customer policy into device-specific commands; and

deploying the device-specific commands to policy targets, wherein each policy target includes an interface assigned a role name associated with the customer policy.

15. (Original) The article of claim 14, wherein executing the instructions further results in:

generating device neutral information associated with the mapping policy, the network policy and the customer policy.

16. (Original) The article of claim 15, wherein the device specific commands are generated from the device neutral information.

17. (Original) The article of claim 15, wherein executing the instructions further results in:

storing the device neutral information in a database.

18. (Original) The article of claim 14, wherein deployment is such that the interfaces associate with at least one of input roles, output roles and MPLS gateways of customer source and destination host groups.

19. (Original) The article of claim 14, wherein

{S:\28212\1200285-us1\80037719.DOC (10/1/2005 15:31 FAX 2082628901) }

Application No.: 10/719,371

7 Docket No.: 28212/1200285-US1/NC34963US

24. (Original) The method of claim 22, further comprising:

storing the device neutral information in a database.

25. (Currently amended) The method of claim 21, wherein

deployment is such that the network interfaces of the policy targets associate with at least one of input roles, output roles and MPLS gateways of customer source and destination host groups.

26. (Currently amended) The method of claim 21, wherein

deploying device-specific commands associated with the mapping policy to the network interfaces of the policy targets further comprises issuing new commands to reconfigure a router based on the mapping policy.

27. (Original) The method of claim 21 wherein

the customer policy includes information about a tunnel group identifier and a tunnel mode.

{S:\28212\1200285-us1\80037719.DOC (USPTO-RECEIVED) (USPTO-RECEIVED) (USPTO-RECEIVED) }